

6. Airstream ASC-TDPM 4 in 1 screw compressor  
(Complete with Certified Tank, Refrigerant dryer and filtration)



6. Airstream ASC-TDPM 4 in 1 screwcompressor  
(Complete with Certified Tank, Refrigerant dryer and filtration)

AIRSTREAM ASC-TDPM 4 - IN 1 ENERGY SAVING COMPRESSOR					
TYPE		ASC010-TDPM	ASC015-TDPM	ASC020-TDPM	ASC030-TDPM
Type of cooling		Air Cooling			
F.A.D m <sup>3</sup> /min	0.8Mpa(8bar)	1.2	1.8	2.3	3.6
	1.0Mpa(10bar)	0.9	1.4	1.8	3
Discharge temp(°C)		≤Ambient temp + 15°C			
Lubricant(L)		5	10	10	15
Noise level dB(A)		72±3			75±3
Driving way		Direct Driven			
Main driver	Kw	7.5	11	15	22
	HP	10	15	20	30
	Starting Method	VSD start			
	Voltage/Frequency	380V/3P/50Hz			
Dimension	Length(mm)	1500	1900	1900	1900
	Width(mm)	810	880	880	970
	Height(mm)	1570	1740	1740	1840
Net weight(kg)		360	520	530	710
Air outlet port size		G3/4"			
Air purified filters		3 grade, 3pcs, 1xQ(=C),1xP(=T),1xS(=A)			
Refrigerant air dryer	P.D.P	2~10□			
	Refrigerant	R134a			
	Volt./Hz.	220V/1PH/50HZ			
Air Tank	Type	Horizontal			
	Standard	CE Certified			
	Capacity	270L	500L		