

Compac dryers (900l/min – 140 000l/min)

COMPAC DRYERS TECHNICAL DATA											
Part number	Bar	m ³ /min	CFM	Length (mm)	Width (mm)	Height (mm)	Weight (KG)	Gas	Connection Size	V/PH/Hz	Filtration
COMPAC 900	16	0,9	31,8	415	330	540	30	R-134a	½"	230/1/50	WITH FILTRATION ATTACHED
COMPAC 1200	16	1,2	42,4	415	330	625	31	R-134a	½"	230/1/50	
COMPAC 1800	16	1,8	63,6	415	330	625	32	R-134a	¾"	230/1/50	
COMPAC 2200	16	2,2	77,7	415	370	670	32	R-134a	¾"	230/1/50	
COMPAC 2600	16	2,6	91,9	555	470	720	44	R-134a	1"	230/1/50	
COMPAC 3100	16	3,1	109,6	555	470	720	45	R-134a	1"	230/1/50	
COMPAC 3700	16	3,7	130,8	555	470	720	47	R-134a	1"	230/1/50	
COMPAC 5500	16	5,5	194,4	720	505	985	79	R-134a	1"	230/1/50	
COMPAC 6500	16	6,5	229,7	720	505	985	83	R-134a	1 ½"	230/1/50	
COMPAC 8500	16	8,5	300,4	905	735	1190	140	R-407c	2"	400/3/50	WITH FILTRATION NOT ATTACHED
COMPAC 11000	16	11	388,7	905	735	1190	140	R-407c	2"	400/3/50	
COMPAC 13000	16	13	459,4	905	735	1190	150	R-407c	2"	400/3/50	
COMPAC 17800	16	17,8	629,1	1145	780	1385	226	R-407c	2 ½"	400/3/50	
COMPAC 20000	16	20	706,8	1145	780	1385	234	R-407c	2 ½"	400/3/50	
COMPAC 25500	16	25,5	901,2	1145	780	1385	273	R-407c	3"	400/3/50	
COMPAC 30000	16	30	1060,2	1450	830	1670	330	R-407c	3"	400/3/50	
COMPAC 35500	16	35,5	1254,6	1450	830	1670	334	R-407c	4"	400/3/50	
COMPAC 40000	16	40	1413,6	1450	830	1670	348	R-407c	4"	400/3/50	
COMPAC 45000	16	45	1590,3	1450	830	1670	480	R-407c	4"	400/3/50	WITHOUT FILTRATION
COMPAC 50000	16	50	1767	1450	830	1670	552	R-407c	4"	400/3/50	
COMPAC 60000	16	60	2120,4	2020	950	1820	700	R-407c	DN-100	400/3/50	
COMPAC 71000	16	71	2509,1	2290	950	2350	800	R-407c	DN-100	400/3/50	
COMPAC 80000	16	80	2827,2	2290	950	2350	950	R-407c	DN-100	400/3/50	
COMPAC 90000	16	90	3180,6	2290	950	2350	1250	R-407c	DN-100	400/3/50	
COMPAC 106 000	16	106	3746	2800	1250	2350	1380	R-407c	DN-125	400/3/50	
COMPAC 120 000	16	120	4240,8	2800	1250	2350	1500	R-407c	DN-125	400/3/50	
COMPAC 140 000	16	140	4947,6	2800	1250	2350	2000	R-407c	DN-125	400/3/50	

Reference Conditions	
Operating Pressure	7 Bar
Operating Temp	35°C
Room Temp	25°C
Pressure Dewpoint	3°C

Limit Conditions	
Max. Working Pressure	16 Bar
Max. Operating Temp	60°C
Min. Room Temp	5°C
Max. Room Temp	50°C